



Atlantis

Atlantis is a thixotropic solvent paint stripper specifically formulated to combine efficiency with low cost. **Atlantis** uses a Haas technology breakthrough to quickly and completely strip paint overspray from walls and floors of the paint booths. This product efficiently strips most types of paint and is particularly effective on high solids enamels and basecoat/clearcoat paints.

Features and Benefits

- Can be applied by spray, roll or brush
- Designed to be easily water washable
- Contains no suspect carcinogens
- Clings to walls for complete overspray removal

Typical Properties

Appearance	Clear, light yellow liquid
Bulk Density	7.5 lbs/gal
Specific Gravity	0.90 @ 70 °F
Solubility	Emulsifies
Flash Point	105 °F
Viscosity	1500-2000 cps @ 75 °F
V.O.C. Content	5.9 lbs./gal.
pH (5% emulsion)	11.0-12.5

Application Procedure

Atlantis is used full strength and is normally applied by spray. A brush or roller will work almost as efficiently. Different applications may require different coating thicknesses. The recommended thickness of the wet film is from 10 to 20 mil. Once applied, Atlantis should be left in contact with the overspray for a minimum of five minutes and as long as twenty minutes before rinsing. Good rinsing can be obtained with normal water pressure, however moderate to high pressures give the best results.